

2031 ROPE ADJUSTER

TECHNICAL SHEET

Positioning lanyards constructed from 12.5 mm polyamide static rope.
Ergonomic squeeze-activated aluminum alloy adjustment device.
Available in a large variety of lengths and configurations to meet the varied needs of workers at height.

NO CONNECTORS

ROOFS

- 203111 2 m
- 203112 5 m
- 203113 10 m
- 203114 20 m



Stitched end with protective layer

STEEL CONNECTORS

TOWERS/INDUSTRY

CONSTRUCTION

- 203115 2 m + 0981 + 0986
- 203116 3 m + 0981 + 0986



Ref.0981

12.5 mm polyamide static rope. EN 1891/A

Ref.0986

CE label with batch and individual serial number

ALU CONNECTORS

ROPE ACCESS

TOWERS/INDUSTRY

- 203117 2 m + 118701 + 0995



Ref.118701

Ref.0995

Tubular protection webbing. Width 40 mm

| Ref. | Product name Nombre del producto | Weight Peso | | CE EN 358 | EAC |
|--------|---------------------------------------|----------------|------|--------------|-----|
| | | g | oz | | |
| 203111 | ROPE ADJUSTER 0.5-2 m | 520 | 18.4 | • | • |
| 203112 | ROPE ADJUSTER 0.5-5 m | 820 | 28.9 | • | • |
| 203113 | ROPE ADJUSTER 0.5-10 m | 1320 | 46.6 | • | • |
| 203114 | ROPE ADJUSTER 0.5-20 m | 2300 | 81.2 | • | • |
| 203115 | ROPE ADJUSTER 0.5-2 m + 0981 + 0986 | 910 | 32.1 | • | • |
| 203116 | ROPE ADJUSTER 0.5-3 m + 0981 + 0986 | 1010 | 35.7 | • | • |
| 203117 | ROPE ADJUSTER 0.5-2 m + 118701 + 0995 | 720 | 25.4 | • | • |